




# SAFE-GAUGE

## INSPECTION CAMERA

### TECHNICAL DATA SHEET



Maximise Safety



Eliminate Live Work



Wireless up to 50m (164ft)



Precision Inspection

## OVERVIEW

The SafeGauge Inspection Camera operates within a WiFi range of up to 50 metres (164ft) allowing users to connect it to the MultiTool Pro.

Each Inspection Camera can be uniquely identified by its serial and product number. Similar to SafeGauge sensors, the MultiTool Pro can connect to a CAM360 providing a live video preview.

With the MultiTool Pro, users can capture photos and record videos, which are then saved directly to the device.

## APPLICATIONS

- Remote monitoring and inspections
- Equipment maintenance and diagnosis

## CAPABILITIES

- Captures 360° videos with 4K resolution
- 50m (164ft) line of sight WiFi range
- Snaps still images
- Removable battery

## STANDARD ACCESSORIES

- 1 x Spare Battery
- 1 x Battery Charger
- 1 x Set of Lens Protectors
- 1 x Camera Sleeve
- 1 x Lens Cleaning Cloth

*\*Additional accessories included in the Inspection Camera Kit (IC-01-MTP) - See page 4.*

**SPECIFICATIONS**

LENS AND MEDIA	
<b>Aperture</b>	F2.4
<b>Image Sensor</b>	1/2.0" (x2), Effective pixels: ~48 MP (x2)
<b>Charging</b>	To be charged by SafeGauge charging case only
<b>Video Resolution</b>	4K: 3840x1920/30fps/100Mbps
<b>File Format</b>	Still Images: JPEG Video: MP4 (MPEG-4 AVC/H.264, AACLC 1ch)
<b>Recording Media</b>	Internal Memory: ~46 GB
<b>Shutter Speed &amp; ISO</b>	Auto/Shutter Priority: ISO50-3200
<b>Exposure Compensation</b>	-2.0 to +2.0 EV (1/3 EV steps)
<b>Charging Time</b>	3 hours (from zero to full charge)

DISPLAY AND CONNECTIVITY	
<b>Display Panel</b>	2.25" TFT Color LCD (360x640), Auto Brightness
<b>Touch Panel</b>	Capacitance Type
<b>Wireless Standards</b>	802.11 a/b/g/n/ac (2.4 GHz / 5 GHz), Bluetooth 5.0.
<b>Interfaces</b>	USB Type C, USB 3.2 Gen 1
<b>Maximum WiFi Range</b>	50 metres (164 feet) line of sight

DISCLAIMER - While every effort has been made to ensure the accuracy of this document at the date of issue, SafeGauge assumes no liability resulting from any omissions or errors in this document, and reserves the right to revise content at any time.

**SPECIFICATIONS**

POWER AND DIMENSIONS	
<b>Power Supply</b>	Rechargeable DB110 (1350 mAh)
<b>Maximum Range</b>	50 metres (164 feet)
<b>Battery Life (4K Video)</b>	~55 minutes
<b>Dimensions</b>	51.7mm (W) x 136.2mm (H) x 29.0mm (D) (~2.0" (W) x 5.4" H x 1.1" D)
<b>Weight</b>	~170grams (with battery and microSD) (~144grams for camera only)

ENVIRONMENTAL	
<b>Operating Temperature Range</b>	0 to 40°C (32 to 104°F)
<b>Operating Humidity Range</b>	< 90%
<b>Storage Temperature Range</b>	-20 to 60°C (-4 to 140°F)

DISCLAIMER - While every effort has been made to ensure the accuracy of this document at the date of issue, SafeGauge assumes no liability resulting from any omissions or errors in this document, and reserves the right to revise content at any time.

## INSPECTION CAMERA KIT CONFIGURATIONS



**12 Channel Field Service Kit**  
7x Pressure Transducers  
1x Dial Indicator  
1x Tachometer  
2x Push Rods  
1x Inspection Camera  
Standard Inspection Camera Accessories  
1x MultiTool Pro



**8 Channel Field Service Kit**  
6x Pressure Transducers  
1x Dial Indicator  
1x Inspection Camera  
Standard Inspection Camera Accessories  
1x MultiTool Pro



**2 Dial Indicator Kit with Inspection Camera**  
2x Dial Indicators  
1x Inspection Camera  
Standard Inspection Camera Accessories  
1x MultiTool Pro



**Inspection Camera Kit**  
1x Inspection Camera  
1x MultiTool Pro

**Additional Accessories Included:**  
1x Dome Protective Case  
1x V-Block  
1x Fall Restraint Cable

*\*Lens Protectors not included*